

#### **INDUSTRIAL VACUUM CLEANERS**





# W 2 - Single phase industrial vacuum cleaner - INDUSTRIAL SINGLE PHASE









✓ Accessories included. Ideal for cleaning contractors.

100% stell construction. Suitable for wet and dry service, also simultaneously. Detachable container with direct bagging option.

SUCTION UNIT			
Voltage	V - Hz	230 - 50	
Power	kW	2 x 1,1	
Max waterlift	mmH2O	2400	
Max air flow	m³/h	360	
Suction inlet	mm	50	

FILTER UNIT			
Filter Type		Star	
Surface - Diameter	cm²-mm	20000	
Cleaning system		Manual	

COLLECTION UNIT		
Collection tank		Steel
Discharge system		Roll-out container
Capacity	lt.	40

VOLUME		
Dimensions	cm	55 x 63 x 115h





## **SUCTION UNIT**

Suction is developed by two carbon brushes by-pass motors which are activated by independent switches placed on a solid, metallic head. Special noise buffers reduce the noise within the safety work standards.



## **FILTER UNIT**

The polyester star filter with large filtration surface placed inside the filter chamber ensures protection from dust and avoids filter clogging.

The filter is cleaned mechanically by means of a manual filter shaking lever which shakes the filter vertically, ensuring safe and effective cleaning. This contributes to maintain high suction efficiency and avoids the spreading of dust in the environment.



# **COLLECTION UNIT**

Suctioned material deposits inside an extractable stainless steel container fitted with wheels, allowing practical and safe emptying. Use with disposable bags is possible.



#### **OPTIONALS**

- ✓ Nomex heat resistant filter up to 250°
- ✓ Absolute Hepa filter H14
- ✓ Accessory basket
- ✓ PTFE coated class M filter
- ✓ Class M teflon hydro-oleophobic filter
- ✓ Antistatic class L filter
- ✓ Antistatic class M filter
- ✓ Stainless steel collection tank and filter chamber
- ✓ Remote control electronic system
- ✓ Earth grounding